

# TECHNICAL SPECIFICATIONS



## Dimensions

|                                    |            |
|------------------------------------|------------|
| Shipping Length                    | 3575mm     |
| Shipping Ground Length             | 1230mm     |
| Shipping Height                    | 2347mm     |
| Shipping Width                     | 990mm      |
| Cab Height                         | 2347mm     |
| Ground Clearance of Counter Weight | 438mm      |
| Min. Ground Clearance              | 150mm      |
| Tail Turning Radius                | 640mm      |
| Wheel Tread                        | 1230mm     |
| Track Length                       | 1590mm     |
| Track Gauge                        | 760/1050mm |
| Track Shoe Width                   | 230mm      |



## Working Range

|                             |        |
|-----------------------------|--------|
| Max. Digging Height         | 3540mm |
| Max. Dumping Height         | 2440mm |
| Max. Digging Depth          | 2310mm |
| Max. Vertical Digging Depth | 1910mm |
| Max. Digging Radius         | 3905mm |
| Max. Ground Digging Radius  | 3845mm |
| Min. Turning Radius         | 1443mm |
| Dozer Blade Lifting Height  | 260mm  |
| Dozer Blade Falling Height  | 180mm  |



## Engine

|                     |                         |
|---------------------|-------------------------|
| Engine Model        | YANMAR 3TNV70-PFN       |
| Number of Cylinders | 3                       |
| Max. Torque/Speed   | 48~51.8/1800±100N·m/rpm |
| Displacement        | 0.854L                  |



## Main Performance

|                      |          |
|----------------------|----------|
| Bucket Digging Force | 15.2kN   |
| Arm Digging Force    | 8.5kN    |
| Max. Traction Force  | 15.5kN   |
| Max. Walking Speed   | 3.7km/h  |
| Min. Walking Speed   | 1.9km/h  |
| Rotary Speed         | 9r/min   |
| Gradeability         | 30°      |
| Ground Pressure      | 32.04kPa |



## Hydraulic system

|                            |         |
|----------------------------|---------|
| Max. Main Pump Flow        | 45L/min |
| Main Safety Valve Pressure | 21.6MPa |



## Other Specifications

|                                 |        |
|---------------------------------|--------|
| Boom Length                     | 1828mm |
| Arm Length                      | 950mm  |
| Track Section Number(each side) | 37     |
| Track Roller Number             | 3      |



## Refill Capacity

|                |       |
|----------------|-------|
| Fuel Tank      | 19L   |
| Hydraulic Tank | 15.4L |
| Engine Oil     | 3.7L  |

## LOVOL HEAVY INDUSTRY GROUP CO.,LTD.

Address:No. 75, Huanghe East Road, Huangdao District, Qingdao City, Shandong Province, China.

Website:en.wlovol.com

As manufacturer, LOVOL has right to constantly upgrade and improve our products without informing to customers. The pictures in literatures are for reference only, the detailed specifications are subject to real products.

# LOVOL



|                  |                    |
|------------------|--------------------|
| Rated Power      | 10.9KW/2400rpm     |
| Operating Weight | 2000kg             |
| Bucket Capacity  | 0.04m <sup>3</sup> |

# FR20F-u

MINI EXCAVATOR